

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 April 2004 (22.04.2004)

PCT

(10) International Publication Number
WO 2004/034619 A2

(51) International Patent Classification⁷:

H04J

(74) Agents: SHAPIRO, Mitchell, W. et al.; Miles & Stockbridge P.C., Suite 500, 1751 Pinnacle Drive, McLean, VA 22102 (US).

(21) International Application Number:

PCT/US2003/032157

(22) International Filing Date: 9 October 2003 (09.10.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/416,925

9 October 2002 (09.10.2002)

US

(71) Applicant (for all designated States except US): ACORN PACKET SOLUTIONS, LLC [US/US]; 2010 Corporate Ridge, Suite 700, McLean, VA 22102 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and


(75) Inventor/Applicant (for US only): SKERRITT, Michael [US/US]; Acom Packet Solutions, LLC, 2010 Corporate Ridge, Suite 700, McLean, VA 22102 (US).

Published:

— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: SYSTEM AND METHOD FOR RATE AGILE ADAPTIVE CLOCKING IN A PACKET-BASED NETWORK



(57) Abstract: A system for transmitting a clock signal through a packet-based network is disclosed. The system comprises a first node configured to measure a clock frequency of the clock signal and calculate an accuracy indicator of the measured clock frequency; a second node configured to receive the clock frequency measurement and the accuracy indicator of the clock frequency measurement, and synthesize the clock signal therefrom; and a packet-based network for transmitting the measured clock frequency and accuracy indicator from the first node to the second node. A method of deriving a clock frequency by identifying packets with the shortest total transmission time is also disclosed.